



Drawing board

oli a ion





3 Characteristic

Forward current	If		30			mA
Reverse voltage	Vr		5			V
Power dissipation	Pd		110			mW
Operating temperature range	Top		-25 +80			C
Storage temperature range	Tg		-30 +80			C
Peak pulsing current 1/8 d f=1KH	Ifp		125			mA
Wavelength at peak emission	If=20mA	peak	515	520	525	nm
Spectral half bandwidth	If=20mA			10		
Forward voltage	If=20mA	Vf	3.0	3.4	3.8	V
Luminous intensity	If=20mA	I	3000	4000	5000	mcd
Viewing angle at 50% IV	If=10mA		--	120	--	Deg





Re er e c rren	Vr=5V	Ir	--	--	5	A
U ef I life	-	IF=20mA	100000			H

Typical Electrical/Optical Characteristic Curve
(Ta=25 Unless Otherwise Noted)



Directivity Characteristic





1	Tin-plated	Temp 260 ± 5	5 sec.	76 PCS	0/1
2	Back & forth under high & low temp alternately	High temp. +85 30min to 5min to -55 30min	50 bo	76 PCS	0/1
3	Heating	High temp. +100 30min To 10 sec to -10 30min	50 bo	76 PCS	0/1
4	High storage temp.	Temperature 100	1000 Hr.	76 PCS	0/1
5	Low storage temp.	-55	1000 Hr.	76 PCS	0/1
6	Life span	VF=1.9V IF=20mA	1000 Hr.	76 PCS	0/1
7	Test under high temp. & high humidity	85 ± 5/85%RH	1000 Hr.	76 PCS	0/1

i Iron Soldering: The Iron (max 30W) end temperature less than 300 °C, soldering time 3 seconds, soldering position is minimum 2mm from body.

ii Dip Soldering: Max temperature is 260 °C, time 5s, the position is minimum 2mm from body.

i Bracket must be bent only if 2mm from colloid.

ii Bracket mold must be finished before or professionally.

iii Bracket mold must be finished before soldering.

i Bracket mold holder should be connected between the pin, the distance gap of lead and the circuit board.

i. It should be paid attention to the ordering of all the devices in case of wrong polarity. Devices can be overlooked or the heat components, working condition can replace the limit.

ii. It should not assemble LED when the lead are deformed.

iii. When decide to assemble in hole, accurately according to the size of hole and hole distance of the line base

i. Suggesting good heating position

i. It should avoid any kind of quake or force on LED, before the soldering temperature returns normal.

It should be very careful. When clean the body with chemical. Some chemical may bring damage to the surface, and bring color fading, such as, Trichloroethylene, Acetone. Should use ethanol or isopropyl, dip for no more than 3 minutes under the normal temperature.



7

